



[www.herbstmachinery.com](http://www.herbstmachinery.com)

## Standard 14 Tonne Rock Trailer



### Standard Features

- Sprung Drawbar
- Heavy Duty EN16 Towing Eye
- Mudguards and Flaps
- Hydraulic Brakes
- Double Acting Drop Down Rear Door

### Optional Features

- Rotary Towing Eye
- Braking System – Air / Oil Options
- Fail Safe Valve / Choke Valve
- Wheels – 550/45 22.5
- Custom Colour



**MODEL**

**14 TONNE ROCK TRAILER**

Permissible Total Weight	18,600kg
Unladen Weight	4,600kg
Cubic Capacity	7.00
Loading Capacity	14,000kg
Maximum Hitch Load	3,500kg
Overall length/Width/Height (mm)	5420 / 2500 / 2300
Loading Height (mm)	2160
Height of inside of Bin (mm)	950
Body Length (mm)	4310
Bin Width Top / Bottom (mm)	2060 / 2020
Bin Thickness Side / Floor / Door	6mm / 10mm / 10mm
Chassis	12"
Running Gear	Heavy Duty 10 Stud Axles on Hi Roc 9 Leaf Spring Suspension
Tyres	385/65 22.5
Wheel Track Width (mm)	2000
Maximum Speed	50KPH
Brake Size	400 X 80
Telescopic Cylinders	2
Telescopic Cylinders (No. Of sections / Stroke / Oil)	3 / 200 Bar / 13.0 Litres
Tipping Angle	71°
Drop Down Rear door	2 x Double Acting Cylinders

**Contact**

**Herbst Machinery Ltd**

120 Drumnakilly Road,  
Omagh,  
Co. Tyrone,  
N. Ireland BT79 0JT

Tel: +44 (0)28 8077 1568

Fax: +44 (0)28 8077 1569

General: [info@herbst.co.uk](mailto:info@herbst.co.uk)

Sales: [ashley@herbst.co.uk](mailto:ashley@herbst.co.uk)

Spare Parts: [stores@herbst.co.uk](mailto:stores@herbst.co.uk)