



www.herbstmachinery.com

Standard 8 / 10 / 12 Tonne Dump Trailer



Standard Features

- Standard Drawbar
- Heavy Duty EN16 Towing Eye
- Mudguards and Flaps
- Hydraulic Brakes

Optional Features

- Sprung Drawbar
- Rotary Towing Eye
- Braking System – Air / Oil Options
- Fail Safe Valve / Choke Valve
- 10mm Floor
- Double Acting Rear Door
- Custom Colour



MODEL	8 TONNE	10 TONNE	12 TONNE
Permissible Total Weight	10,080Kg	12,450Kg	14,750Kg
Unladen Weight	2,080	2,450kg	2,760kg
Cubic Capacity	4.75	5.20	6.00
Loading Capacity	8,000kg	10,000kg	12,000kg
Maximum Hitch Load	3,500kg	3,500kg	3,500kg
Overall length / Width / Height (mm)	4612 / 2200 / 2015	5000 / 2225 / 2070	5150 / 2225 / 2190
Loading Height (mm)	1765	1830	1940
Height of inside of Bin (mm)	905	905	1010
Body Length (mm)	3468	3797	3797
Bin Width Top / Bottom (mm)	2020 / 1350	2020/1350	2075 / 1425
Bin Thickness Side / Floor	6mm / 6mm	6mm / 6mm	6mm/ 6mm
Chassis	8"	8"	8"
Running Gear	1 x 8 Stud Axle (90 x 90 Beam)	Rocker Beams - 8 Stud Hubs (80 x 80 Beam)	Rocker Beams - 8 Stud Hubs (80 x 80 Beam)
Tyres	385 / 65 22.5	385 / 65 22.5	385 / 65 22.5
Wheel Track Width (mm)	1850	1920	1920
Maximum Speed	50KPH	50KPH	50KPH
Brake Size (mm)	350 X 60	350 X 60	350 X 60
Telescopic Cylinders	1	2	2
Telescopic Cylinders (No. Of sections / Stroke / Oil)	3 / 200 Bar / 13.0 Litres	3 / 200 Bar / 9.73 Litres	3 / 200 Bar / 9.73 Litres
Tipping Angle	71°	71°	71°
Up & over Rear door	1 x Single Acting Cylinder	1 x Single Acting Cylinder	1 x Single Acting Cylinder

Contact

Herbst Machinery Ltd

120 Drumnakilly Road,
 Omagh,
 Co. Tyrone,
 N. Ireland BT79 0JT

Tel: +44 (0)28 8077 1568

Fax: +44 (0)28 8077 1569

General: info@herbst.co.uk

Sales: ashley@herbst.co.uk

Spare Parts: stores@herbst.co.uk