



www.herbstmachinery.com

Standard 19 Tonne Gross Bale Trailer



Standard Features

- Standard Drawbar
- Parking Brake
- Hay Ladders—Front & Rear
- Rope Hooks
- Side Crash Barriers
- Mud Guards—Front & Rear

Optional Features

- Sprung Drawbar
- High Speed Running Gear
- Dual Air / Hydraulic Braking
- Headboard
- Steel Chequered / Smooth Floor
- Tool Box—Front / Side
- Custom Colour



Bale Trailer 19 Tonne Gross	20'	22'	24'	26'	28'	30'	32'
Permissible Total Weight	19,000kg	19,000kg	19,000kg	19,000kg	19,000kg	19,000kg	19,000kg
Carrying Capacity	15,000Kg	15,000Kg	15,000Kg	15,000Kg	15,000Kg	15,000Kg	15,000Kg
Unladen Weight	2,660Kg	3,000kg	3,340Kg	3,680Kg	4,020Kg	4,660Kg	5,060Kg
Overall Length/Width/Height (mm)	7725 / 2500 / 2250	8350 / 2500 / 2250	8970 / 2500 / 2250	9590 / 2500 / 2250	10215 / 2500 / 2250	10840 / 2500 / 2250	11460 / 2500 / 2250
Platform Length / Height (mm)	6225 / 1070	6850 / 1070	7470 / 1070	8090 / 1070	8715 / 1070	9340 / 1070	9960 / 1070
Floor	50mm Timber	50mm Timber	50mm Timber	50mm Timber	50mm Timber	50mm Timber	50mm Timber
Wheel Track Width (mm)	1850	1850	1850	1850	1850	1850	1850
No. of Axles	2 x 8 Stud	2 x 8 Stud	2 x 8 Stud	2 x 8 Stud	2 x 8 Stud	2 x 8 Stud	2 x 8 Stud
Axle Load	9000kg	9000kg	9000kg	9000kg	9000kg	9000kg	9000kg
Maximum Hitch Load	3,500kg	3,500kg	3,500Kg	3,500Kg	3,500Kg	3,500Kg	3,500Kg
Chassis	8"	8"	8"	8"	8"	12"	12"
Braking System	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking
Brake Size (mm)	300 x 90	300 x 90	300 x 90	300 x 90	300 x 90	300 x 90	300 x 90
Axle suspension	Hi-Roc 7 Leaf Springs	Hi-Roc 7 Leaf Springs	Hi-Roc 7 Leaf Springs	Hi-Roc 7 Leaf Springs	Hi-Roc 7 Leaf Springs	Hi-Roc 8 Leaf Springs	Hi-Roc 8 Leaf Springs
Tyre Dimensions	435/50 19.5	435/50 19.5	435/50 19.5	435/50 19.5	435/50 19.5	435/50 19.5	435/50 19.5
Maximum Speed	50 KPH	50 KPH	50 KPH	50 KPH	50 KPH	50 KPH	50 KPH
Drawbar Towing Eye	50mm Fixed Ring	50mm Fixed Ring	50mm Fixed Ring	50mm Fixed Ring	50mm Fixed Ring	50mm Fixed Ring	50mm Fixed Ring

Contact

Herbst Machinery Ltd

120 Drumnakilly Road,
 Omagh,
 Co. Tyrone,
 N. Ireland BT79 0JT

Tel: +44 (0)28 8077 1568

Fax: +44 (0)28 8077 1569

General: info@herbst.co.uk

Sales: ashley@herbst.co.uk

Spare Parts: stores@herbst.co.uk