



www.herbstmachinery.com

Standard Livestock Trailer



Standard Features

- Parking Brake
- Mud Guards—Front & Rear
- Side Crash Barriers
- Galvanised Slurry Box
- Solid Ribbed Roof
- Dividing Gates
- Inspection Door
- Aluminium Sides / Steel Chequered Floor

Optional Features

- High Speed Running Gear
- Dual Air / Hydraulic Braking
- 215/75 17.5 Twin Wheels
- Lift Off Option
- Tool Box—Front / Side
- Custom Colour



Livestock Trailer	18'	20'	22'	24'	26'	28'	30'
Permissible Total Weight	12,000kg	12,000kg	19,000kg	19,000kg	19,000kg	19,000kg	19,000kg
Unladen Weight	3,460Kg	3,700kg	4,100Kg	4,540Kg	5,000Kg	5,460Kg	6,160Kg
Overall Length/Width/Height (mm)	7250 / 2470 / 2970	7725 / 2470 / 2970	8350 / 2470 / 3020	8970 / 2470 / 3020	9590 / 2470 / 3020	10215 / 2470 / 3020	10840 / 2470 / 3020
Floor	5mm Steel Chequered "Anti Slip"	5mm Steel Chequered "Anti Slip"	5mm Steel Chequered "Anti Slip"	5mm Steel Chequered "Anti Slip"	5mm Steel Chequered "Anti Slip"	5mm Steel Chequered "Anti Slip"	5mm Steel Chequered "Anti Slip"
Wheel Track Width (mm)	1800	1800	1850	1850	1850	1850	1850
No. of Axles	2 x 6 Stud	2 x 6 Stud	2 x 8 Stud	2 x 8 Stud	2 x 8 Stud	2 x 8 Stud	2 x 8 Stud
Axle Load	5,500kg	5,500kg	9,000kg	9,000kg	9,000kg	9,000kg	9,000kg
Maximum Hitch Load	3,500kg	3,500kg	3,500Kg	3,500Kg	3,500Kg	3,500Kg	3,500Kg
Chassis	8"	8"	8"	8"	8"	8"	12"
Braking System	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking	Hydraulic - All wheel Braking
Brake Size (mm)	300 x 60	300 x 60	300 x 90	300 x 90	300 x 90	300 x 90	300 x 90
Axle suspension	Hi-Roc 5 Leaf Springs	Hi-Roc 5 Leaf Springs	Hi-Roc 7 Leaf Springs	Hi-Roc 7 Leaf Springs	Hi-Roc 7 Leaf Springs	Hi-Roc 8 Leaf Springs	Hi-Roc 8 Leaf Springs
Tyre Dimensions	400/60 15.5	400/60 15.5	435/50 19.5	435/50 19.5	435/50 19.5	435/50 19.5	435/50 19.5
Maximum Speed	40 KPH	40 KPH	50 KPH	50 KPH	50 KPH	50 KPH	50 KPH
Drawbar Towing Eye	50mm Fixed Ring	50mm Fixed Ring	50mm Fixed Ring	50mm Fixed Ring	50mm Fixed Ring	50mm Fixed Ring	50mm Fixed Ring
Drawbar	Standard	Standard	Sprung	Sprung	Sprung	Sprung	Sprung

Contact

Herbst Machinery Ltd

120 Drumnakilly Road,
 Omagh,
 Co. Tyrone,
 N. Ireland BT79 0JT

Tel: +44 (0)28 8077 1568

Fax: +44 (0)28 8077 1569

General: info@herbst.co.uk

Sales: ashley@herbst.co.uk

Spare Parts: stores@herbst.co.uk