



www.herbstmachinery.com

Heavy Duty Tri Axle Low Loader 33 Tonne Gross



Standard Features

- Payload 25,000kg +
- Running Gear 3 x 10 Stud Full Commercial Axles
- Air / Hydraulic Brakes complete with Load Sensing Valve
- Heavy Duty 12" Chassis
- 12° Rounded Beavertail
- Pull Outriggers
- Sprung Drawbar
- Rear Lights on Ramp & Inside Well of Beavertail (+Flasher on each Ramp, complete with On/Off switch)
- Mudguards Front and Rear
- Side Tool Box
- Floor 50mm Soft Wood
- 600mm Wide Heavy Duty Hydraulic Ramps with Gripper Bars

Optional Features

- Towing eye Type – Standard Ring, K80 Spoon, Rotary Eye
- Towing Eye – Adjustable Height / Rotary / Adjustable & Rotary
- Braking System – ABS, Fail Safe Valve
- Bale Wedge
- Closed Beavertail
- Swing Outriggers
- Wide Ramps – Maximum 900mm
- Bolsters
- 3mm Steel Strips under Timbers for supporting Wheeled Machines
- Commercial Jack Legs, Hydraulic / Manual Jack Leg
- Tool Box – Front
- Colour



Model	Heavy Duty Tri Axle Low Loader
Permissible Total Weight	33,000kg
Carrying Capacity	26,500kg
Unladen Weight	6,500kg
Overall Length/Width/Height (mm)	10100 / 2500 / 2480
Length of Flat Platform (mm)	6400
Length of Beavertail (mm)	1620
Ramp - Length / Width (mm)	1800 / 600
Height of Platform (mm)	950
Floor	50mm Swedish Kiln Dried Soft Wood
Wheel Track Width (mm)	1820
No. of Axles	3 x Commercial
Axle Manufacturer	Granning / HOS
Axle Load	11,000kg
Maximum Hitch Load	3,500kg
Braking System	Air/Oil complete with Load Sensing
Brake Size (mm)	310 x 190
Axle suspension	Hi-Roc 8 Leaf Springs Suspension
Tyre Dimensions	235/75 17.5 New J Rated
Maximum Speed	50 KPH
Drawbar Towing Eye	Heavy Duty 50mm Fixed Ring

Contact

Herbst Machinery Ltd

120 Drumnakilly Road,
Omagh,
Co. Tyrone,
N. Ireland BT79 0JT

Tel: +44 (0)28 8077 1568

Fax: +44 (0)28 8077 1569

General: info@herbst.co.uk

Sales: ashley@herbst.co.uk

Spare Parts: stores@herbst.co.uk