



# 19T Gross Low Loader



## HERBST 19T LOW LOADER

*Strong. Practical. Built for everyday haulage.*

- 19,000 kg gross trailer weight
- Approx. 15,000 kg payload
- Twin axle low loader
- Sprung, lowered loading ramps
- Well-in beavertail design
- All-wheel hydraulic braking
- Suitable for plant & machinery transport

### Optional Features:

- Sprung drawbar
- Adjustable or rotary towing eye
- Commercial axles (10-stud, up to 105 KPH)
- Air / oil braking with ABS
- Hydraulic ramps or tail lift
- Toolboxes, custom colour & length options

### Applications:




Plant & Machinery  
Transport, Construction,  
Agriculture, Forestry &  
Landscaping



**Built to your specification.**  
*Scan to chat with our team  
on WhatsApp.*

## 19T Low Loader Overview



-  Versatility.
-  Innovation.
-  Performance.

### Technical Specifications:

- **Weights (kg):** 19,000 gross · 15,360 payload · 3,640 unladen
- **Overall Size (mm):** 20FT 8450 / 2500 / 2300 · 24FT 9440 / 2500 / 2300
- **Flat Platform Length (mm):** 20FT 4750 · 24FT 5750
- **Beavertail Length (mm):** 1620
- **Ramp Size (mm):** 1650 / 600
- **Platform Height (mm):** 930
- **Wheel Track Width (mm):** 1850
- **Floor:** 50mm Swedish kiln-dried softwood
- **Axles:** 2 × 8 stud · ADR · 9,000 kg · Leaf sprung
- **Braking:** Hydraulic all-wheel braking · 300 × 90
- **Tyres / Speed:** 215/75 R17.5 (New J Rated) · 50 KPH
- **Maximum Hitch Load:** 3,500 kg

*Dimensions shown for 20ft + 24ft models, other lengths available on request*

