



Operating Mode

FEATURES & BENEFITS

- 900 x 450 Jaw Crusher
- Crush Size 40mm - 125mm
- Designed for material up to 400mm
- HD Compact Chassis on Twin Axle
- PTO Direct Drive
- Minimum Tractor Requirement - 120HP
- Crusher RPM Sensor with Override Warning Signal
- Manual Hydraulic Operated Jaw Opening Adjustment
- Removable Discharge Conveyor
- Direct Feed Hopper
- Platform for Service / Maintenance Access
- HD Hydraulic Operated Stability Jack Legs

HERBST AGRI CRUSHER	
Unladen Weight (Kg)	12,250
Transport Length / Width / Height (mm)	6920 (22' 8") / 2500 (8' 2") / 3460 (11' 4")
Working Length (mm)	8900 (29' 2") Plus Tractor Unit
Jaw Size (mm)	900 x 450 (36" x 18")
Crush Size (mm)	40 - 125 (1 1/2" - 5")
Hopper Width / Length (mm)	2185 (7' 2") / 1700 (5' 7")
Feed Height from Ground Level (mm)	3000 (9' 10")

NEW

HERBST

Product Leaflet



AG900

900 Agri Crusher

This unit has a 900 x 450 Jaw aperture and is gravity fed direct from the hopper. Crush Size is regulated by hydraulic adjustment on the jaw. The aggressive crushing provides effective throughput of material onto the discharge conveyor, where material is stockpiled at the rear. This conveyor is removable, facilitating access and maintenance. The unit also has an access platform to the feed hopper, for inspection and maintenance as and when required.

Herbst 900 Agri Crusher



Versatility on any project work

Running costs minimised

Setup time practically eliminated

Simplicity in Operation

Easily towed from site to site

Suitable for small, confined spaces

Simple, yet robust with exceptional output



HERBST MACHINERY LTD

120 Drumnakilly Road,
Omagh, Co. Tyrone, N. Ireland. BT79 0JT

Tel: +44 (0)28 8077 1568

Fax: +44 (0)28 8077 1569

Mob: +44 (0) 79000 80380

General: info@herbst.co.uk

Sales: ashley@herbst.co.uk



Available Worldwide