



www.herbstmachinery.com

Gravel Trailer - Material Distribution



Standard Features

- Payload 8,000 Kg
- Heavy duty tapered hopper
- Hydraulic opening on material outlet
- Telescopic conveyor with option to discharge on either side
- Heavy duty 8 Stud axle
- 16.9 x 30 Agri Tread wheels

Optional Features

- Extension Sides
- 23.1 R26 wheels
- Additional side conveyor
- Colour



Model	Gravel Trailer
Permissible Total Weight	10,220kg
Carrying Capacity	8,000kg
Unladen Weight	2,220kg
Overall Length/Width/Height (mm)	51000 / 2300 / 2200
Width of Hopper @ Side (mm)	2740 (9Ft)
Width of Hopper @ Rear (mm)	2135 (7Ft)
Loading Height (mm)	2200
Outlet Opening Width (mm)	300
Conveyor Load Width (mm)	400 - 450 (600mm Belt)
Discharge Height (mm)	950 on standard wheel option
Discharge Distance from Wheel	Estimated 1050mm on standard wheel option
Wheel Track Width (mm)	1850
No. of Axles	1 x 8 Stud
Axle Manufacturer	ADR
Axle Load	9,500kg
Maximum Hitch Load	3,500kg
Braking System	Hydraulic
Brake Size (mm)	300 x 90
Tyre Dimensions	16.9 x 30 Agricultural Tread
Maximum Speed	40 KPH
Drawbar Towing Eye	Heavy Duty 50mm Fixed Ring

Contact

Herbst Machinery Ltd

120 Drumnakilly Road,
Omagh,
Co. Tyrone,
N. Ireland BT79 0JT

Tel: +44 (0)28 8077 1568

Fax: +44 (0)28 8077 1569

General: info@herbst.co.uk

Sales: ashley@herbst.co.uk

Spare Parts: stores@herbst.co.uk