



FEATURES & BENEFITS

- Tractor Towed with Tractor PTO Powered Hydraulics
- 700 x 400 Jaw Crusher
- Simple Hydraulic Adjustment on Crush Size
- Sensor Controlled Grizzly feeder
- Removable Discharge Conveyor
- Option for Over Band Magnet
- Crusher RPM Indicator with Override Protection Function
- Time Clock
- Platform for Service / Maintenance Access
- Hydraulic Operated Stability Jack Legs complete with Lock Valves
- Minimum Tractor Requirement - 120HP

HERBST HAC700 CRUSHER	
Unladen Weight (Kg)	11,500 (Includes Magnet)
Transport Length / Width / Height (mm)	7050 (23' 1") / 2350 (7' 8") / 3250 (10'8")
Working Length (mm)	8400 (27' 6") Plus Tractor Unit
Jaw Size (mm)	700 x 400 (28" x 16")
Crush Size (mm)	40 - 100 (1 1/2" - 4")
Feed Hopper for Grizzly - Length / Width (mm)	2200 (7' 3") / 1600 - 1400 (5'3" - 4'7")
Feed Height from Ground Level (mm)	2800 (9' 2")
Stockpile Height (mm)	2200 (7'3")

NEW

HERBST

Product Leaflet



HAC 700

Crusher

This unit has a 700 x 400 Jaw aperture with a sensor controlled grizzly feeder, optimising throughput and making it more user friendly for the operator. Crush Size is regulated by hydraulic adjustment on the jaw. The aggressive crushing provides effective throughput of material onto the discharge conveyor, where material is stockpiled at the rear. This conveyor is removable, facilitating access and maintenance. The unit also has an access platform to the grizzly feeder, for inspection and maintenance as and when required.



Versatility on any project work

Running costs minimised

Setup time practically eliminated

Simplicity in Operation

Towed by Agricultural Tractor with
PTO Powered Hydraulics

Easily towed from site to site

Suitable for small, confined spaces

HERBST

HERBST MACHINERY LTD

120 Drumnakilly Road,
Omagh, Co. Tyrone, N. Ireland. BT79 0JT

Tel: +44 (0)28 8077 1568

Fax: +44 (0)28 8077 1569

Mob: +44 (0) 79000 80380

General: info@herbst.co.uk

Sales: ashley@herbst.co.uk



www.herbstmachinery.com