

FEATURES & BENEFITS

- 700 x 400 Jaw Crusher
- Crush Size 40—100
- Designed for material up to 350mm
- HD Compact Chassis on Wheels
- PTO Direct Drive
- Minimum Tractor Requirement 100HP
- Crusher RPM Sensor with Overide Warning
 Signal
- Manual Hydraulic Operated Jaw Opening
 Adjustment
- Removable Discharge Conveyor
- Feed Hopper
- Platform for Service / Maintenance Access
- Hydraulic Operated Stability Jack Legs

HERBST AGRI CRUSHER

| Unladen Weight (Kg) | 7900 |
|---|---|
| Transport Length / Width / Height (mm) | 5900 (19' 4") / 2350 (7' 8") / 3100 (10'2") |
| Working Length (mm) | 7350 (24' 2'') Plus Tractor Unit |
| Jaw Size (mm) | 700 × 400 (28" × 16") |
| Crush Size (mm) | 40 - 100 (1 ¹ / ₂ " - 4") |
| Hopper Width / Length (mm) | 1870 (6' 2") / 1725 (5' 8'') |
| Feed Height from Ground Level | 2800 (9' 2") |







www.herbst machinery.com

The Herbst Agri Crusher is a gravity fed jaw crusher with a 700 x 400 Jaw aperture. Crush Size is regulated by hydraulic adjustment on the jaw. The aggressive crushing provides effective throughput of material onto the discharge conveyor, where material is stockpiled at the rear. This conveyor is removable, within 5 minutes, facilitating access and maintenance. The unit also has an access platform to the feed hopper, for inspection and maintenance as and when required. RPM Monitor indicates crusher running speed, facilitating setup for crushing.



Versatility on any project work Running costs minimised Setup time practically eliminated Simplicity in Operation Easily towed from site to site

Suitable for small, confined spaces

Exceptional Crushing Capability for both Small & Large Scale Projects



HERBST MACHINERY LTD

I 20 Drumnakilly Road, Omagh, Co. Tyrone, N. Ireland. BT79 0JT

> Tel: +44 (0)28 8077 1568 Fax: +44 (0)28 8077 1569 Mob: +44 (0)79000 80380 General: info@herbst.co.uk Sales: ashley@herbst.co.uk

> > Available Worldwide

www.herbstmachinery.com