



www.herbstmachinery.com

Super 16T / Super 14T DT



Standard Features

Heavy Duty EN16 Towing Eye / Sprung Drawbar / Hose Tidy

10mm Floor

D/A Drop Down Flat Rear Door (10mm Floor)

Twin Multi Stage Tipping Cylinders

10 Stud High Speed Axles (420 x 180)

Air & Hydraulic Brakes with Load Sensing

560/60 22.5 Flotations Super Singles

Mud Flaps / LED Lighting Kit

Optional Features

Rotary Towing Eye / 80mm Spoon Hitch / Bolt On

Wheels – 445/65 22.5 Super Singles

Tool Box

Roll Over Sheeting Systems

Custom Colour



MODEL	SUPER 14T	SUPER 16T
Cubic Capacity (m3)	7.0	8.6
Loading Capacity - Aggregate (Kg)	14,000	16,000
Maximum Hitch Load (Kg)	3,500	3,500
Overall length/Width/Height (mm)	6428 / 2605 / 2100	6428 / 2605 / 2300
Loading Height @ Sides (mm)	1950	2150
Loading Height @ Rear (mm)	1350	1350
Height of inside of Bin (mm)	600	800
Inside Body Width (mm)	2318	2318
Body Thickness Side / Floor	6mm / 10mm	6mm / 10mm
Chassis	RHS	RHS
Running Gear	10 Stud / Mono Spring	10 Stud / Mono Leaf Spring
Tyres	560/60 22.5	560/60 22.5
Wheel Track Width (mm)	2000	2000
Maximum Speed	50KPH	50KPH
Brake Size (mm)	420 x 180	420 x 180
Telescopic Tipping Cylinder	2 x Multi Stage	2 x Multi Stage
Drop Down Flat Rear door	2 x D/A Cylinders	2 x D/A Cylinders

Contact

Herbst Machinery Ltd

120 Drumnakilly Road,
Omagh,
Co. Tyrone,
N. Ireland BT79 0JT

Tel: +44 (0)28 8077 1568

General: info@herbst.co.uk

Sales: ashley@herbst.co.uk

Spare Parts: stores@herbst.co.uk